

## **TECHNICAL DATA**

## FILTER CARTRIDGE SPECIFICATIONS

**ITEM NUMBER: 1567080** 

Dimensions: Height: 26"
Outside Diameter: 17.61"

Inside Diameter: 14.00"

Top End Cap: Material: Electro Galvanized (22 ga)

Style: Open with 18.82" lip flange

Bottom End cap: Material: Electro Galvanized (22 ga)

Style: Closed

Gasket: 11/16" x 1/2" x 17.75" ID mounted under flange

Inner Retainer: Electro galvanized expanded metal 3/8" x 5/8"

72% open area with hot melt beads. Includes liner

with spring retainer

Outer Retainer: Electro galvanized expanded metal 3/8" x 5/8" 72%

open area with hot melt beads

Filter Media Area: 226 ft<sup>2</sup>

Pleat Count: 419

Media Type: Cellulose/ 100% PP Meltblown

Permeability: 22 cfm/ft² @ 0.5" w.g.

176 L/sec/m² @ ΔP 20 mm w.g.

Maximum Temperature: 180° F

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

PARTICLE SIZE: 0.5 micron----- 99.8%

1.0 micron----- 99.9% 2.0 micron----- 100 %